



### **CONTENTS**

- 1. WLAN History and Challenges
- 2. H3C WLAN & Solutions
- 3. H3C Innovative WLAN Technologies
- 4. H3C WLAN Products and O&M Platform
- 5. H3C WLAN Tolly certification






# **History of Wi-Fi Technology**



# WiFi-6 Speed 872.7 Times Faster than WiFi-1



# **WLAN Scenarios**















# WLAN faces multiple challenges



### **Challenge 1: Diversified Wi-Fi deployment solutions**

### **Indoor Scenario**

•Offices, classrooms, exhibition halls, hotels, dormitories, and hospital wards scenes are clearly differentiated, and it is difficult to adapt to a single solution



### **Outdoor Scenario**


- Outdoor long-distance coverage
- •Outdoor high temperature and rain environment, equipment reliability and stability requirements are high;





### Railway & Stadiums

- High-density stadiums
- •Rail transit 120Km/h+ fast switching





# WLAN faces multiple challenges



### Challenge 2: Wi-Fi technology bottlenecks affect user experience

### **High density access**

User concurrency rate is high, network resource scheduling is unreasonable,



# High reliability of network equipment

Lack of redundant backup, poor user service reliability.

# High requirements for mobile user experience

Poor terminal roaming, frequent online and offline, user fatigue, and poor Internet experience.

### Wi-Fi Bottlenecks

### Wireless security


There is a lot of interference in the wireless environment, and rogue terminals and hacker attacks threatennetwork security.

# WLAN faces multiple challenges



Challenge 3: Network planning, installation, and maintenance restrict large-scale deployment

# Complex network planning and design





•The on-site environment is complex and diverse, and it is difficult for engineers to deal with it manually

# Complex equipment installation



•The large number of APs and complex installation result in huge waste of labor and time costs

# Inconvenient network O&M





•Network operation status is difficult to assess, and faults are difficult to locate





# No.1 Market Share in China and Niche Player WW



IDC Report : 31.12% market share





Figure 1. Magic Quadrant for the Wired and Wireless LAN Access Infrastructure



# **High-quality WLAN and Service Resources**



750+
Wireless Patents



2 Billion R&D Investment


500+
R&D WLAN Staff

6 R&D Centers 4000+
Partners in WW



### **H3C Wi-Fi Solutions**






H3C Wi-Fi with deep accumulation, innovative technology and diversified deployment solutions provides the users best experience



# Centralized traffic forwarding mode





#### Scenario

- User data and authentication are centrally processed by AC
- AP/AC supports cross-layer 2 and layer 3 networking

#### AC

- AP, user DHCP server
- Unified configuration of AP parameters
- Unified user policy configuration
- User authentication control point

#### **User Auth**


- Policy Center
- Portal server
- Radius server
- MAC authentication server

#### **Network O&M**

- AC web page network management
- IMC+WSM
- AC/AP network management

# Local traffic forwarding mode





#### **Scenario**

- It is suitable for branch office network. Save link bandwidth between AP/AC
- Both the customer gateway and the DHCP server are in the local network
- Local forwarding user authentication can be handled centrally by AC
- AP/AC supports cross-layer 2 and layer 3 networking

#### AC

- AP, user DHCP server
- Unified configuration of AP parameters
- Unified user policy configuration
- User authentication control point

#### **User Authen**


- Policy Center
- Portal server
- Radius server
- MAC authentication server

#### **Network O&M**

- AC web page network management
- IMC+WSM
- AC/AP network management

# Traffic mixed forwarding mode





#### Scenario

- ■realize forwarding by AP and forwarding by SSID. If the headquarters uses the centralized forwarding mode, the branch office network uses the local forwarding mode
- User authentication in both modes is handled centrally by AC
- AP/AC supports cross-layer 2 and layer 3 networking

#### AC

- AP, user DHCP server
- Unified configuration of AP parameters
- Unified user policy configuration
- User authentication control point

#### **User Authen**

- Policy Center
- Portal server
- Radius server
- MAC authentication server


#### **Network O&M**

- AC web page network management
- IMC+WSM
- AC/AP network management



### **Indoor scenarios**





#### **Scenarios**

Enterprise office, classroom, lobby, exhibition hall, etc.

### **Product Selection**

Indoor AP: WA5300,WA6300,6600 series

High density: Tri-radio AP

High-end AC: WX38,WX58 series

Low-end AC: WX18 series

### **Highlights**

- ■The full range of 802.11ac/11ax APs can be flexibly matched to meet the requirements of different deployment scenarios
- A variety of ACs meet the management needs of different scales of wireless networks
- AC 1+1 hot backup, N+1 redundant backup

# Wall-plate indoor scenarios





### **Easy Deployment**

- 86mm international standard
- 3 minutes installation
- Cost of installation reduced by 50%





### **High Speed**


- 2.4G/5G Dual band
- Support 2\*2 MU-MIMO
- 1.2G+0.575 high bandwidth

### Multi-ports

1 uplink and 4 Gigabit LAN ports for additional IP devices

# **Indoor X-share scenario**





### **Scenarios**

Warehouse, corridor,dormitory

### **Product Selection**

WA6620X,WA6628X,WA6526E

### **Highlights**

Flexible deployment and cost-saving

# Warehouse case







It is recommended that the AP be placed on the end of the shelf


The height of the panel antenna is 3 meters, and it is tilted downward to the aisle

WA6620X,WA6628X,WA6526E
 support this solution since they all
 have external antenna port

The cable can be pasted on the shelf and it is not allowed to cross the shelf (because the forklift will scratch it)







#### **Scenario**

Teaching buildings, dormitory buildings, libraries, plazas, public hotspots, pedestrian streets, etc.

### **Highlights**


- AP has no external lightning protection device is required
- AP is easy to install, improve engineering efficiency and reduce labor costs

#### **Product**

- WA6620X
- WA6628X
- WA6630X


# **Outdoor long-distance deployment**





# **Outdoor bridging scenario**





#### **Scenarios**

In areas where wiring is inconvenient, WDS and MESH networking can be used instead of wired links to achieve data bridging and coverage

#### **Product**


Wi-Fi 6 AP

### **Highlights**

- Outdoor AP no external lightning protection device is required
- Outdoor AP is easy to install, improving engineering efficiency and reducing labor costs
- Support Mesh network load balancing based on link quality

# Outdoor industrial design adapts to various harsh environments








Meet various harsh environmental requirements
High stability and reliability
Cost savings





# Railway Wi-Fi solution





### **Fast Switching**

- Vehicle-ground communication fast switching technology
- ■160Km/h+ per hour, switching time <30ms, "zero" packet loss

### **High Bandwidth**

- The latest generation of 802.11ax rail transit products
- 1G wireless bandwidth between vehicle and ground


### **Stable**

Professional Anti-vibration design

# **Professional Anti-vibration design**







### **Standards**


**EMC:**EN50121-3-2

**Anti-vibration** IEC61373

Fire and flame retardant EN/DIN 5510

# High-density stadiums deployment plan





 Different stadium scenes need to flexibly choose a combination of deployment methods according to the on-site environment



# **WRRM-Automatic RF Optimization**




Dynamic channel adjustment


Dynamic power adjustment

Dynamic load balancing


interference
assessment

Illegal device interference











 Automatic channel deployment, shorten deployment time, and flexibly respond to network changes •Automatically adjust the transmission power to avoid interference and fill in blind spots Balance access resources within and between APs to improve overall network performance

•Automatic channel interference tuning to improve the transmission performance of the system in an interference

•Automatic detection of illegal equipment, automatic optimization of wireless parameters, and

# **High Density Booster-SACP, RROP**





Low speed terminal Access control Multi-user Conflict control


WMM Qos


Airtime Fairness Low speed terminal Access control


Multi-user CAC Scheduling












•Restrict lowspeed terminal access and improve air interface efficiency •Adjust the terminal competition, reduce conflicts, and improve transmission efficiency

Wireless QoS scheduling, important business first  Let users share wireless fairly and transmit more data ·Low-speed terminals automatically limit offline, improving air interface efficiency •Coordination of roaming resources on the entire network to maintain reasonable AP utilization

# **Smart Antenna-Smart antenna array**





**Traditional wireless network** 

**Smart antenna array** 

### **Smart antenna advantage:**

- 1. increase AP coverage distance and reduce the number of APs deployed
- Intelligent control of AP coverage to reduce interference between adjacent Aps
- 3. Adjust wireless phase to increase AP gain
- 4. Signal sensitive switching to ensure wireless signal quality

# **User Awareness-terminal recognition**





Brand A-Computer



Brand B-Computer



Brand C-Phone




Phone

#### **Policy based on terminal type**

According to the terminal type, the authentication page is automatically adapted,

Assign different policys according to the terminal type such as VLAN/ACL/bandwidth limit



AP

■AC through terminal MAC address, HTTP, User-Agent information and DHCP option to identify vendors and terminal types

> **Authentication message carries** terminal type information



**Policy Center** 

#### Distribute policy based on terminal types

■Deliver policy based on the reported terminal type information

■Restriction, user isolation strategy



Laptop



Pad

Same account, different terminal types of policy

■Support the same user account allocation according to terminal type


Different business strategies, detailed user authority control granularity





# User Awareness - dynamic user group authorization





### **Employee group policy configuration**

■Bandwidth authorization: 1Mbps

**Guest group policy configuration** 

- ■ACL authorization: denied access to internal resources
- Service VLAN: Guest service VLAN
- ■User isolation: communication between users is prohibited

- ■Bandwidth authorization: 4Mbps
- ■ACL authorization: can access the company's business platform
- ■Service VLAN: employee service VLAN
- ■User isolation: allow users in the group to communicate, prohibit
- ■Stop user communication between groups

**①** User Authentication




② Radius sends user groups to AC



③ AC enforces user group policy

# Converged wireless security solutions





#### Security on the wireless side

- Spectrum analysis of non-Wi-Fi devices
- WIDS/WIPS
- Wireless attack detection
- Rogue device identification countermeasures

### **Data protection backup**

- •DTLS (Datagram TLS) real-time encryption protection
- Standard CAPWAP wireless tunnel protocol
- AC1+1 hot backup, N+1 backup
- AC upstream IPsec tunnel

### Multiple authentication access schemes

- Multiple access control methods such as MAC/802.1X/Portal
- Portal + MAC hybrid authentication
- WPA2,WPA3

## Seamless roaming-seamless perception



### Seamless roaming, uninterrupted business



### Fast roaming in the second and third layers of AC

- Meet the roaming needs of users in different forwarding modes
- Fast switching, uninterrupted business, no need to reauthenticate users

### Seamless roaming between the second and third layers of AC

- Meet the roaming needs of users in different forwarding modes
- seamless switching,
   uninterrupted business, no
   need to re-authenticate

### Seamless indoor and outdoor roaming


Seamless indoor and outdoor roaming

Wi-Fi-Phone

Professional network
 planning to achieve wireless
 roaming in the park

### Remote AP-Continuous service





#### **① CAPWAP disconnect**

After the CAPWAP link is interrupted, online user services will not be interrupted, and data will continue to be forwarded

#### **② New Users Online**


■When the security policy on the wireless side of the AP is open syste m authentication, shared key authe ntication (WEP), and WPA/WPA2-PS K, new online users can access and go online. User data is forwarded th rough the local forwarding mode.

#### **Scenarios**

■For small wireless networks without AC backup, the service life mode can ensure uninterrupted user data forwarding and improve service reliability .

## **AC 1+1 IRF-High reliability**





#### IRF

AC address virtual: facing the AP, the active and standby ACs use one AC address

#### **Business real-time backup**


- User data information backup
- CAPWAP tunnel information backup
- AP table entry backup


### 1+1 hot standby switch detection


- ① AC whole machine inspection
- ② AC Uplink Detection(BFD)

## AC N+1 redundant backup









#### **Scenarios**

■In a large-scale campus scenario where multiple ACs are deployed at the same time, use the N+1 backup function to improve the reliability of the overall network service and reduce the purchase cost of AC equipment


#### N+1 backup

- ■The backup AC provides backup services for all main ACs at the same time
- Support automatic active/standby AC switching and state recovery




### **H3C WLAN Product Family**





### **H3C CloudNet Solution**







### ZTP Deployment on site

- Zero touch provisioning
- Stateless connection
- GUI, easy handle



### Cloud Management

- Cloud o&m, visualization
- Oasis app, light-weight
- AI, Big data




Value-added

- Marketing
- Flexible authentication
- Open API

## **AD-Campus Unified Wired & Wireless Solution**





### Unified Management

SDN architecture

One-key deployment

Multi-service AC card in core switch

### Unified Forwarding

Unified wired and wireless network users

Wireless local forwarding

Unified monitoring and controlling outlet traffic

### Unified Policy

Wired and wireless group policy delivered by Director to L3 GW

Unified security policy delivered to Firewall


Whether wired or wireless, IP remaining unchanged while roaming in campus

## **WSM-Wireless Service Management**



### **iMC WSM (Wireless Service Management)**

- Unified topology management
- RF signal coverage management
- Wireless security management
- Wireless statistical report
  - Performance index
  - Warning and alarm index
- User management
  - Username and IP/MAC address
  - Signal intensity
  - RSSI/SSID/Channel, etc.



**Wired & Wireless Unified Topology** 



**Wireless RF Coverage Management** 

## **WBC Super Controller**







#### **Multi-service**

- ■AC cluster, license sharing, entire network AP and access virtualization
- Wireless coverage ISSU, live upgrade
- Roaming center
- Open platform, can flexibly support third-party business

#### **Smart O&M**

- Site survey, deployment, acceptance
- ■Doctor AP simulates terminal services in real time, self-checking network
- Problem identification and self-healing
- Progressive optimization




# Wi-Fi 6 Indoor Flagship AP-WA6628/WA6638





#### 12 Spatial streams/Tri-radio



**Highest single-client wireless** throughput, representing the fastest Wi-Fi connection speed that has been tested by Tolly

#### **High performance**, reliability




Dual PoE ports (hot backup on ports)



DTLS for hardware secure



Multi-rate 10GE+1GE, improve reliability and availability



 External IoT: suitable for IoT clear goals in the initial stage of network construction

Built-in IoT: Suitable for unclear current needs but future IoT needs.



**Built-in/external** IoT module



WA6628 supports up to 100 clients to simultaneously stream 4K videos smoothly







# **Tolly Report**



Product	Tolly Verified
WA6638	
WA6628	<ol> <li>5GHz radio Wi-Fi 6 single user performance, HE80, 8x8:8 mode single user performance ≥4.145Gbps HE160, 4x4:4 mode single user performance ≥4.176Gbps, a third-party test report issued by an authoritative laboratory is required</li> <li>Multimedia concurrency performance, each terminal has a throughput of at least 2Mbps, the device can support ≥450 terminals at the same time smooth on-demand</li> <li>4K video performance, each terminal has a throughput of at least 30Mbps, the device can support ≥100 terminals at the same time and smoothly</li> <li>The throughput of the device is 10 terminals with 5GHz radio frequency, and 5 terminals with 2.4GHz radio frequency. The maximum throughput of the device is ≥4.5Gbps</li> </ol>
WA6622	1. The product supports MU-MIMO, SU-MIMO performance ≥980Mbps, MU-MIMO performance ≥1840Mbps, MU-MIMO is 1.8 times of SU-MIMO performance
WA6330	<ol> <li>Multimedia concurrency performance, each terminal has a throughput of at least 1Mbps, and the device can support ≥610 terminals simultaneously and smoothly</li> <li>The throughput of the device is 5GHz radio frequency 10 terminals, and the 2.4GHz radio frequency 5 terminals, the maximum throughput of the device ≥1.78Gbps</li> <li>5GHz radio frequency Wi-Fi 6 single-user performance, HE80, UDP traffic in 2x2:2 mode, 5GHz radio 1: Upstream performance ≥948Mbps, Downstream ≥948Mbps; 5GHz Radio 2: Upstream ≥945Mbps, Downstream ≥ 945Mbps</li> </ol>
WA6320	<ol> <li>Concurrency performance, each terminal has a throughput of at least 2Mbps, the device can support ≥350 terminals at the same time and smoothly</li> <li>The throughput of the device is 5GHz radio frequency 10 terminals, the 2.4GHz radio frequency 5 terminals, the maximum throughput of the device ≥1Gbps</li> </ol>



